

# The `graphicx` package\*

D. P. Carlisle      S. P. Q. Rahtz

2021/09/16

This file is maintained by the L<sup>A</sup>T<sub>E</sub>X Project team.  
Bug reports can be opened (category `graphics`) at  
<https://latex-project.org/bugs.html>.

## 1 Introduction

This package provides an alternative interface to the L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub>  graphics functions. The command names provided are the same as in the standard package, and they use the same internal functions. However the meaning of the optional arguments is different. Note *only* the optional arguments have changed: any document which only uses the graphics commands with the mandatory arguments and/or the star-forms will work identically (with essentially identical implementation) with the two packages.

## 2 Key=Value Interface

When the decision to produce L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub>  was made, certain ‘guiding principles’ were made (and published in the original announcement). One of these was that all new features would ‘conform to the conventions of version 2.09’. Specifically this meant that new commands would obey the same basic syntax rules for arguments as the existing commands.

Standard L<sup>A</sup>T<sub>E</sub>X optional arguments are *positional*. If a command were to take three optional arguments, then there would be no way of specifying only the third, one would have to give all three, even if the first two were repeats of the default values. Basically this means that ‘standard’ optional arguments are not suitable if there is more than one option. Various existing packages (for L<sup>A</sup>T<sub>E</sub>X 2.09) have recognised this, and used ‘named arguments’ in various forms. Perhaps the two most noticeable are `psfig` and `pstricks`. With ‘named arguments’ (sometimes called ‘attributes’) each option is not tied to a particular position, but rather given a name (or key) and any options that must be set are set by explicitly associating this name with the desired value.

The members of the L<sup>A</sup>T<sub>E</sub>X Project do appreciate the importance of this kind of syntax, but felt that rather than extending the syntax of L<sup>A</sup>T<sub>E</sub>X in an uncoordinated way, it would be better to keep with ‘standard arguments’ in L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub> , which is

---

\*This file has version number v1.2d, last revised 2021/09/16.

intended as a ‘consolidation of existing L<sup>A</sup>T<sub>E</sub>X variants’. The long term planning for an eventual L<sup>A</sup>T<sub>E</sub>X3 release will then be able to consider the whole L<sup>A</sup>T<sub>E</sub>X user interface, and a suitable syntax for named arguments. It is important that such an interface design is not hampered by having to retain compatibility with earlier attempts at a named argument syntax. For this reason this `graphicx` package, which uses the named argument mechanism from the `keyval` package should be considered ‘non standard’ although it is supported by the same mechanism, and same authors as the ‘standard’ `graphics` package.

### 3 The User Interface

```
\includegraphics *{[<key-val list>]}{<file>}
\includegraphics *{[<llx, lly>]}{[<urx, ury>]}{<file>}
Include a graphics file.
```

The star form is just for compatibility with the standard interface, and essentially just adds `clip` to the keys specified. Similarly the second, two-optional argument form is for increased compatibility with the standard package. The two optional argument form is not needed in the `keyval` interface.

Various ‘keys’ or named arguments are supported.

**bb** Set the bounding box. The argument should be four dimensions, separated by spaces.

**bbllx,bbly,bburx,bbury** Set the bounding box. Mainly for compatibility with older packages. `bbllx=a,bbly=b,bburx=c,bbury=d` is equivalent to `bb = a b c d`.

**natwidth,natheight** Again an alternative to `bb`. `natheight=h,natwidth=w` is equivalent to `bb = 0 0 h w`.

**viewport** Modify the bounding box specified in the file. The four values specify a bounding box *relative* to the `llx, lly` coordinate of the original box.

**trim** Modify the bounding box specified in the file. The four values specify the amounts to remove from the left, bottom, right and top of the original box.

**hiresbb** Boolean valued key. Defaults to `true`. Causes T<sub>E</sub>X to look for `%%HiResBoundingBox` comments rather than the standard `%%BoundingBox`. May be set to `false` to override a default setting of `true` specified by the `hiresbb` package option.

**angle** Rotation angle.

**origin** Rotation origin (see `\rotatebox`, below).

**width** Required width, a dimension (default units `bp`). The graphic will be scaled to make the width the specified dimension.

**height** Required height. a dimension (default units `bp`).

**totalheight** Required totalheight (i.e., height + depth). a dimension (default units `bp`). Most useful after a rotation (when the height might be zero).

**keepaspectratio** Boolean valued key (like `clip`). If it is set to true, modify the meaning of the `width` and `height` (and `totalheight`) keys such that if both are specified then rather than distort the figure the figure is scaled such that neither dimension *exceeds* the stated dimensions.

**scale** Scale factor.

**clip** Either ‘true’ or ‘false’ (or no value, which is equivalent to ‘true’). Clip the graphic to the bounding box (or viewport if one is specified).

**draft** a boolean valued key, like ‘clip’. locally switches to draft mode, ie. do not include the graphic, but leave the correct space, and print the filename.

**type** Specify the file type. (Normally determined from the file extension.)

**ext** Specify the file extension. *Only* for use with `type`.

**read** Specify the ‘read file’ which is used for determining the size of the graphic. *Only* for use with `type`.

**command** Specify the file command. *Only* for use with `type`.

**quiet** Turns off writing information about graphics to the `.log`.

**page** The page of a multi-page PDF graphic to be used.

**interpolate** Enables interpolation of bitmap images by viewers.

**pagebox** Specifies which PDF box should be used for the natural image size, one of mediabox, cropbox, bleedbox, trimbox, artbox. The default is driver-specific.

The arguments are interpreted left to right. `clip`, `draft`, `bb`, and `bbllx` etc. have the same effect wherever they appear. but the scaling and rotation keys interact.

Any scaling that is specified *before* rotation, is handled by the internal graphics inclusion function. Rotation, or any later scaling is handled by implicitly calling `\rotatebox` or `\scalebox`. So `[height=1in,angle=90]` scales the graphic to 1in, then rotates it, so it is one inch wide. `[angle=90,height=1in]` first rotates, then scales the result so that it is 1in high. A driver that can scale included graphics, but not arbitrary text will not be able to support the second form, as it will require a call to `\scalebox`, but the first form should work as there the scaling is handled by `\Ginclude@graphics`.

**\rotatebox** [`{key-val list}`] {`<angle>`} {`<text>`}

Rotate `text`.

The keys supported by `\rotatebox` are:

**origin** Specify the centre of rotation. `origin=<label>`, where the labels are up to two of `1rctbB` (B denotes the baseline, as for PStricks).

**x,y** An alternative to `origin`. `x=<dimen>,y=<dimen>` The  $x, y$  coordinate of the centre of rotation. As usual `\height` etc may be used.

**units** Specify the units used in the main argument. eg `units=-360` would mean that the argument referred to degrees *clockwise* instead of the default anti-clockwise rotation.

As an example `\rotatebox[origin=c]{180}{text}` will rotate “text” around its centre, thus creating a final box of the same dimensions as the original box. This is to be contrasted to the default behaviour, which rotates around the reference point on the baseline, thus producing a box that is mainly *below* the baseline.

## 4 Implementation

```
1 <*package>
```

One new option is handled by keyval. It suppresses the error normally generated if an unknown keyval key is used. (This helps porting between drivers that use extended interfaces.)

```
2 \DeclareOption{unknownkeysallowed}
3   {\PassOptionsToPackage{\CurrentOption{keyval}}}
```

All other options are handled by the `graphics` package.

```
4 \DeclareOption*{\PassOptionsToPackage{\CurrentOption{graphics}}}
5 \ProcessOptions
```

This package requires these two building blocks.

```
6 \RequirePackage{keyval,graphics}
```

### 4.1 Graphics Inclusion

First we declare the ‘bounding box’ keys. These all use `\Gin@defaultbp` so that the `<value>` can be given as a length in the usual TeX units such as `cm` or as an integer, taken as `bp`.

```
\KV@Gin@bb
7 \define@key{Gin}{bb}
8   {\Gin@bboxtrue\Gread@parse@bb#1 \\}
```

```
\KV@Gin@bbllx
\KV@Gin@bbly
\KV@Gin@bburx
9 \define@key{Gin}{bbllx}
10   {\Gin@bboxtrue\Gin@defaultbp\Gin@llx{\#1}}
\KV@Gin@bbury
11 \define@key{Gin}{bbly}
12   {\Gin@bboxtrue\Gin@defaultbp\Gin@lly{\#1}}
13 \define@key{Gin}{bburx}
14   {\Gin@bboxtrue\Gin@defaultbp\Gin@urx{\#1}}
15 \define@key{Gin}{bbury}
16   {\Gin@bboxtrue\Gin@defaultbp\Gin@ury{\#1}}
```

`\KV@Gin@hiresbb` If set to true (the default) TeX will look for bounding box comments of the form `%%HiResBoundingBox` (which typically have real values) instead of the standard `%%BoundingBox` (which should have integer values). It may be set to false to override a package option of `hiresbb`.

```
17 \define@key{Gin}{hiresbb}[true]{%
18   \edef\Gread@BBox{%
19     \@percentchar\@percentchar
20     \csname if#1\endcsname HiRes\fi
21     BoundingBox}}
```

```
\KV@Gin@natheight
\KV@Gin@natheight
22 \let\KV@Gin@natwidth\KV@Gin@bburx
23 \let\KV@Gin@natheight\KV@Gin@bbury
```

\KV@Gin@viewport	A ‘viewport’ is a user-specified area of the graphic to be included. It should not be confused with the ‘Bounding Box’ of a PS file. In fact, the origin for a viewport specification is the (llx,lly) lower left coordinate of the bounding box. If a viewport is specified, and clipping is turned on, clipping is based on the viewport, not on the boundingbox.
\KV@Gin@trim	Both ‘viewport’ and ‘trim’ were suggested (and originally, but differently, implemented) by Arthur Ogawa.
	<pre> 24 \define@key{Gin}{viewport} 25   {\let\Gin@viewport@code\Gin@viewport\Gread@parse@vp#1 \\} 26 \define@key{Gin}{trim} 27   {\let\Gin@viewport@code\Gin@trim\Gread@parse@vp#1 \\} </pre>
\Gread@parse@vp	Grabs four bounding box values like \Gread@parse@bp but saves them in alternative macros that are used in the viewport and trim cases to modify the bounding box read from the file.
	<pre> 28 \def\Gread@parse@vp#1 #2 #3 #4 #5\\{% 29   \Gin@defaultbp\Gin@vllx{#1}% 30   \Gin@defaultbp\Gin@vlly{#2}% 31   \Gin@defaultbp\Gin@vurx{#3}% 32   \Gin@defaultbp\Gin@vury{#4}}% </pre>
\KV@Gin@angle	Specify a rotation. This is just handled by wrapping the \includegraphics command in a call to the internal version of \rotatebox. Normally this is the ‘standard’ version but if an <code>origin</code> key is used in \includegraphics then the <code>keyval</code> version of <code>origin</code> is used, and the <code>origin</code> key is passed on.
	<pre> 33 \define@key{Gin}{angle} 34   {\Gin@esetsize 35    \@tempswattrue 36    \edef@\tempa{\toks@{\noexpand\Gin@erotate{#1}{\the\toks@}}}% 37    \@tempa} </pre>
\KV@Gin@origin	Pass the <code>origin</code> key value on to \rotatebox. \Gin@erotate is initialised to \Grot@box@std later in the file, after the latter has been defined.
	<pre> 38 \define@key{Gin}{origin}[c]{% 39   \def\Gin@erotate{\Grot@box@kv[origin=#1]}} </pre>
\KV@Gin@width	Save the required height and width. The actual scaling is done later.
\KV@Gin@height	<pre> 40 \define@key{Gin}{width}{\def\Gin@ewidth{\#1}} 41 \define@key{Gin}{height}{\def\Gin@eheight{\#1}} </pre>
\KV@Gin@totalheight	The same as <code>height</code> key, but locally changes \Gin@eresize to \totalheight from its default value of \height.
	<pre> 42 \define@key{Gin}{totalheight}{% 43   \def\Gin@eresize{\totalheight}\def\Gin@eheight{\#1}} </pre>
\KV@Gin@keepaspectratio	Boolean valued key (like <code>clip</code> ). If it is set to true, modify the meaning of the <code>width</code> and <code>height</code> (and <code>totalheight</code> ) keys such that if both are specified then rather than distort the figure the figure is scaled such that neither dimension <i>exceeds</i> the stated dimensions.
	<pre> 44 \define@key{Gin}{keepaspectratio}[true]{% 45   \lowercase{\Gin@boolkey{\#1}}{iso}} </pre>

\KV@Gin@scale	If the scaling is being handled externally, wrap \includegraphics in the internal form of \scalebox, otherwise locally define \Gin@req@sizes to calculate the required sizes based on scale factor.
	<pre> 46 \define@key{Gin}{scale}{% 47   \if@tempswa 48     \edef\@tempa{\toks@\noexpand\Gscale@box{\#1}[\#1]{\the\toks@}}% 49     \@tempa 50   \else 51     \def\Gin@req@sizes{% 52       \def\Gin@scalex{\#1}\let\Gin@scaley\Gin@exclamation 53       \Gin@req@height\Gin@scalex\Gin@nat@height 54       \Gin@req@width\Gin@scalex\Gin@nat@width}% 55   \fi 56   \@tempswatrue} </pre>
\KV@Gin@draft	Locally set the draft switch to true. This is used by the code in graphics package to suppress the file inclusion.
	<pre> 57 \define@key{Gin}{draft}[true]{% 58   \lowercase{\Gin@boolkey{\#1}}{draft}} </pre>
\KV@Gin@clip	Locally set the clip switch to true. This is used by the code in graphics package to suppress the printing of anything outside the bounding box specified.
	<pre> 59 \define@key{Gin}{clip}[true]{% 60   \lowercase{\Gin@boolkey{\#1}}{clip}} </pre>
\KV@Gin@type	If you use ‘type’ you must use no extension in the main argument and you must use ‘ext’. You can also use ‘read’ and ‘command’.
	<pre> 61 \define@key{Gin}{type}{% 62   \def\Ginclud@graphics##1{% 63     \begingroup 64     \def\Gin@base{\#1}% 65     \edef\@tempa{\#1{\Gin@eread}{\Gin@ecom{\#1\Gin@eext}}}% 66     \expandafter\Gin@setfile\@tempa 67   \endgroup} </pre>
\KV@Gin@ext	Specify an extension, for use with the ‘type’ key.
	<pre> 68 \define@key{Gin}{ext}{\def\Gin@eext{\#1}} 69 \let\Gin@eext\empty </pre>
\KV@Gin@read	Specify a read file, for use with the ‘type’ key. You may want to globally set this to * using \setkeys. * means read the graphic file for size info, as in \DeclareGraphicsRule.
	<pre> 70 \define@key{Gin}{read}{% 71   \def\Gin@eread{\#1}% 72   \def\@tempa{*}\ifx\@tempa\Gin@eread\def\Gin@eread{\Gin@eext}\fi} 73 \let\Gin@eread\empty </pre>
\KV@Gin@command	Specify a command, for use with the ‘type’ key.
	<pre> 74 \define@key{Gin}{command}{\def\Gin@ecom##1{\#1}} 75 \let\Gin@ecom\firstofone </pre>

\KV@Gin@decodearray	For manipulating bitmap images.
	76 \define@key{Gin}{decodearray}{% 77   \def\Gin@decode{\#1}% 78 }
\KV@Gin@quiet	Skip writing to the log.
	79 \define@key{Gin}{quiet}[]{}% 80   \let\Gin@log\@gobble 81 }
\KV@Gin@page	Page of a multi-page (PDF) graphic.
	82 \define@key{Gin}{page}{% 83   \def\Gin@page{\#1}% 84   \ifx\Gin@page\@empty 85   \else 86     \edef\Gin@page{\number\Gin@page}% 87   \fi 88 }
\KV@Gin@interpolate	Enable/disable interpolation of bitmap images by the viewer.
	89 \define@key{Gin}{interpolate}[true]{% 90   \lowercase{\Gin@boolkey{\#1}{interpolate}}}
\KV@Gin@pagebox	Specify which PDF box to use for the natural image size in PDF inclusions.
	91 \define@key{Gin}{pagebox}{% 92   \expandafter\let\expandafter\Gin@pagebox 93     \csname Gin@pagebox@\#1\endcsname 94   \ifx\Gin@pagebox\relax 95     \let\Gin@pagebox\Gin@pagebox@cropbox 96     \@warning{ 97       Unknown value ‘#1’ for ‘pagebox’. \MessageBreak 98       Supported values: \MessageBreak 99       mediabox, cropbox, bleedbox, trimbox, artbox% 100     }}% 101   \fi 102 } 103 \def\Gin@pagebox@mediabox{mediabox}% 104 \def\Gin@pagebox@cropbox{cropbox}% 105 \def\Gin@pagebox@bleedbox{bleedbox}% 106 \def\Gin@pagebox@trimbox{trimbox}% 107 \def\Gin@pagebox@artbox{artbox}%
\KV@Gin@alt	By default the <code>alt</code> key does nothing but may be used for alternative text for accessibility uses in extensions.
	108 \define@key{Gin}{alt}{}
\Gin@boolkey	Helper function for defining boolean valued functions. The order of arguments allows <code>\lowercase</code> to only act on the user-supplied argument.
	109 \def\Gin@boolkey#1#2{ 110   \csname Gin@\#2\ifx\relax#1\relax true\else#1\fi\endcsname}
\Gin@esetsize	Arrange for the final size to be set, either by wrapping the include graphics call in <code>\scalebox</code> , or by redefining <code>\Gin@req@sizes</code> appropriately.

```

111 \def\Gin@eresize{\height}
112 \def\Gin@esetsize{%
113   \let\@tempa\Gin@exclamation
114   \if@tempswa
```

External. Wrap the `\includegraphics` command in a call to the internal form of `\scalebox` to handle the rotation.

```

115   \edef\@tempa{\toks@\{\noexpand
116     \Gscale@{\box\noexpand\Gin@eresize
117       {\Gin@ewidth}{\Gin@eheight}{\the\toks@}}\}%
118     \atempa
119   \else
```

Internal. Handle scaling with the `\includegraphics` command directly rather than calling `\scalebox`.

```

120   \ifx\Gin@ewidth\@tempa
121     \ifx\Gin@eheight\@tempa
```

No resizing.

```
122   \else
```

Just height specified.

```

123   \let\Gin@@eheight\Gin@eheight
124   \def\Gin@req@sizes{%
125     \Gscale@{\div\Gin@scaley\Gin@@eheight\Gin@nat@height}
126     \let\Gin@scalex\Gin@exclamation
127     \setlength\Gin@req@height\Gin@@eheight
128     {\Gin@req@width\Gin@scaley\Gin@nat@width}\%
129   \fi
130   \else
131     \ifx\Gin@eheight\@tempa
```

Just width specified.

```

132   \let\Gin@@ewidth\Gin@ewidth
133   \def\Gin@req@sizes{%
134     \Gscale@{\div\Gin@scalex\Gin@@ewidth\Gin@nat@width}
135     \let\Gin@scaley\Gin@exclamation
136     \setlength\Gin@req@width\Gin@@ewidth
137     {\Gin@req@height\Gin@scalex\Gin@nat@height}\%
138   \else
```

Both height and width specified.

```

139   \let\Gin@@ewidth\Gin@ewidth
140   \let\Gin@@eheight\Gin@eheight
```

At this point can locally redefine `\Gin@nosize`. Instead of generating an error, just set the ‘natural’ size to be the ‘requested size’. Previous versions of this package did not allow the use of `height` and `width` unless the natural size was known as otherwise L<sup>A</sup>T<sub>E</sub>X can not calculate the scale factor. However many drivers (especially for bitmap formats) can work this out themselves, so as long as both `height` and `width` are given, so L<sup>A</sup>T<sub>E</sub>X knows the size to leave, accept this. This assumes the code in the driver file will use the ‘required height’ information, not the scale factors, which will be set to 1!.

```

141   \def\Gin@nosize##1{%
142     \KV@Gin@nat@width\Gin@@ewidth
143     \KV@Gin@nat@height\Gin@@eheight}\%
```

```

144      \def\Gin@req@sizes{%
145          \Gscale@div\Gin@scalex\Gin@@ewidth\Gin@nat@width
146          \Gscale@div\Gin@scaley\Gin@@eheight\Gin@nat@height

```

Donald Arseneau requested this feature. If both `height` and `width` are chosen, choose the smaller scale factor rather than distort the graphic. This mode is turned on with the `keepaspectratio` key.

```

147      \ifGin@iso
148          \ifdim\Gin@scaley>\Gin@scalex\p@%
149              \let\Gin@scaley\Gin@scalex
150          \else
151              \let\Gin@scalex\Gin@scaley
152          \fi
153      \fi
154      \Gin@req@width\Gin@scalex\Gin@nat@width
155      \Gin@req@height\Gin@scaley\Gin@nat@height}%
156      \fi
157      \fi
158  \fi
159  \let\Gin@ewidth\Gin@exclamation
160  \let\Gin@eheight\Gin@ewidth

```

`\Gin@req@height` The required final size.

```

\Gin@req@width 161 \newdimen\Gin@req@height
                162 \newdimen\Gin@req@width

```

`\Gin@outer@scalex` Scale factors to pass to `\scalebox`.

```

\Gin@outer@scaley 163 \let\Gin@outer@scalex\relax
                    164 \let\Gin@outer@scaley\relax

```

`\Gin@angle` Rotation angle.

```
165 \let\Gin@angle\relax
```

`\Gin@ewidth` Final size, initialised for no scaling.

```

\Gin@eheight 166 \let\Gin@ewidth\Gin@exclamation
                167 \let\Gin@eheight\Gin@ewidth

```

`\Gin@scalex` Scale factors. Initialised for no scaling.

```

\Gin@scaley 168 \def\Gin@scalex{1}
                169 \let\Gin@scaley\Gin@exclamation

```

`\Gin@i` Use the same top level `\includegraphics` command as the standard interface. This will set the clipping switch, and then call `\Gin@i`.

```

170 \def\Gin@i{%
171   \def\Gin@req@sizes{%
172     \Gin@req@height\Gin@nat@height
173     \Gin@req@width\Gin@nat@width}%
174   \ifeqnextchar[\Gin@iif[\Gin@ii[]]}}

```

`\Gin@ii` Look for a second optional argument. If one optional argument is present, call `\setkeys` to process it,

```

175 \def\Gin@ii[#1]#2{%
176   \def\@tempa{}{\def\@tempb{#2}}%

```

```

177   \ifx\@tempa\@tempb
178     \def\@tempa{\Gin@iii[#1][]%
179       \expandafter\@tempa
180   \else
181     \begingroup
182       \tempswafalse
183       \toks@{\Gin@include@graphics{#2}}%
184       \setkeys{Gin}{#1}%
185       \Gin@esetsize
186       \the\toks@
187   \endgroup
188   \fi}

```

## 5 Rotation

```

\rotatebox Look for an optional argument.
189 \protected\def\rotatebox{%
190   \leavevmode
191   \Grot@box@kv\Grot@box@std}

\Grot@box@std If no KV argument, just repeat the standard definition.
192 \long\def\Grot@box@std#1#2{%
193   \Grot@setangle{#1}%
194   \setbox\z@\hbox{\#2}%
195   \Grot@x\z@
196   \Grot@y\z@

```

```
\Grot@box@kv
198 \long\def\Grot@box@kv[#1]#2#3{%
199   \begin{tempboxa}\hbox{#3}%
200     \Grot@x\width \divide\Grot@x\tw@
201     \Grot@y\height \advance\Grot@y-\depth \divide\Grot@y\tw@
202     \setkeys{Grot}{#1}%
203     \setboxz@box\@tempboxa
204     \Grot@setangle{#2}%
205     \Grot@box
206   \end{tempboxa}
```

There are two ways of specifying the centre of rotation.

\KV@Grot@origin   origin=⟨label⟩, where the labels are up to two of lrctbB (B denotes the baseline, as for PSTricks).

```
207 \define@key{Grot}{origin}[c]{%
208   \atfor@\tempa:=#1\do{%
209     \if l@\tempa \Grot@x\z@\else
210     \if r@\tempa \Grot@x\width\else
211     \if t@\tempa \Grot@y\height\else
212     \if b@\tempa \Grot@y-\depth\else
213     \if B@\tempa \Grot@v\z@\fi\fi\fi\fi\fi}
```

`\KV@Grot@x` `x=<dimen>,y=<dimen>` The  $x,y$  coordinate of the centre of rotation. As usual  
`\KV@Grot@y` `\height` etc may be used.

```

214 \define@key{Grot}{x}{\setlength{\Grot@x{#1}}}
215 \define@key{Grot}{y}{\setlength{\Grot@y{#1}}}

\KV@Grot@units 'units' specifies the number or units in one anti-clockwise circle. So the default is
360. -360 gives clockwise rotation, 6.283185 gives radians etc.
216 \define@key{Grot}{units}{%
217   \def\Grot@setangle##1{%
218     \dimen@##1\p@
219     \dimen@ii#1\p@
220     \divide\dimen@ii360\relax
221     \divide\dimen@\dimen@ii
222     \edef\Grot@angle{\number\dimen@}}}

\Gin@erotate Initialise the rotation command to use in \includegraphics.
223 \let\Gin@erotate\Grot@box@std

224 </package>

```